

<b>SPRAY APPLICATOR</b>	<b>UFD FIBERIZED SPRAY</b>	<b>UFD EQUITY FIBERIZED SPRAY</b>	<b>UFD HIGH-SPEED FIBERIZED SPRAY</b>	<b>DELTA FX FIBERIZED SPRAY</b>	<b>ULTRA SCS HIGH-SPEED STRAND COATING</b>	<b>ULTRA SPRAY HIGH-SPEED FIBERIZED SPRAY</b>	<b>VECTOR METERED SPRAY ADAPTER</b>
<b>MIN./MAX. NO. OF MODULES</b>	1-6	1-14 / segment	1-6	2	1-8	1-8	1-40
<b>SPACING BETWEEN NOZZLE CENTERS</b>	25 mm (.98 in)	25.2 mm (.99 in)	25 mm (.98 in)	N/A	1-3 strands	25 mm (.98 in)	25 mm (.98 in)
<b>TEMPERATURE RANGE</b>	38°C to 218°C (100°F to 425°F)	38°C to 218°C (100°F to 425°F)	38°C to 218°C (100°F to 425°F)	38°C to 200°C (100°F to 392°F)	38°C to 200°C (100°F to 392°F)	38°C to 200°C (100°F to 392°F)	38°C to 218°C (100°F to 425°F)
<b>WARM-UP TIME</b>	15 min. (cold start) 5 min. (module change)	30 min. (cold start) 5 min. (module change)	15 min. (cold start) 5 min. (module change)	15 min. (cold start) 5 min. (module change)	15 min. (cold start) 5 min. (module change)	15 min. (cold start) 5 min. (module change)	30 min. (cold start) 10 min. (module change)
<b>ADHESIVE VISCOSITY</b>	100 to 30,000 cps	100 to 30,000 cps	100 to 30,000 cps	Lab Test Required	100 - 30,000 cps	100 - 30,000 cps	500 to 30,000 cps
<b>MAXIMUM ADHESIVE PRESSURE</b>	68 bar (1,000 psi)	68 bar (1,000 psi)	68 bar (1,000 psi)	68 bar (1,000 psi)	68 bar (1,000 psi)	68 bar (1,000 psi)	68 bar (1,000 psi)
<b>PROCESS AIR PRESSURE RANGE</b>	0 - 2.7 bar (0-40 psi)	0 - 2.7 bar (0-40 psi)	0 - 2.7 bar (0-40 psi)	0.8 to 1.5 bar (12-22 psi)	0 to 1.7 bar (0 to 25 psi)	1 to 4 bar (15 to 58 psi)	0 to 2.7 bar (0 to 40 psi)
<b>SUPPLY VOLTAGE</b>	200-240 VAC 1 Phase 50-60Hz	200-240 VAC 1 Phase 50-60Hz	200-240 VAC 1 Phase 50-60Hz	200-240 VAC 1 Phase 50-60Hz	200-240 VAC 1 Phase 50-60Hz	200-240 VAC 1 Phase 50-60Hz	200-240 VAC 1 Phase 50-60Hz
<b>DIMENSIONS (HxDxW)</b>	261 x 146.3 x 50-150 mm (10.28 x 5.76 x 1.97-5.91 in)	269 x 222 x 151-350 mm (9.31 x 8.74 x 5.95 in) / segment	133.5 x 216.2 x 50-150 mm (5.25 x 8.51 x 1.97 - 5.91 in)	310 x 171 x 70,3 mm (12.2 x 6.73 x 2.76 in)	146 x 235 x 50-200 mm (5.75 x 9.26 x 1.97-7.87 in)	146 x 235 x 50-200 mm (5.75 x 9.26 x 1.97-7.87 in)	272 x 222 x 700-1600 mm (10.71 x 8.74 x 27.56-63.03 in)

Note: All above information is dependent on line speed operation and type of adhesive, some results may vary.