

	<b>BF MARATHON</b> Slot Die	<b>EquityC</b> Slot Die	<b>EquityC NC</b> Slot Die	<b>APEX</b> Slot Die	<b>CrossCoat</b> High Precision Slot Die	<b>TwinCoat</b> High Precision Dual Slot Die	<b>Vector</b> Metered Slot Die
<b>Slot Die Applicator</b>							
<b>Contact vs. Non-Contact</b>	Contact	Contact	Non-Contact	Contact	Non-Contact	Non-Contact	Contact
<b>Operating Temperature</b>	38°C to 218°C (100°F to 425°F)	38°C to 200°C (100°F to 392°F)	38°C to 200°C (100°F to 392°F)	38°C to 200°C (100°F to 392°F)	38°C to 200°C (100°F to 392°F)	38°C to 200°C (100°F to 392°F)	38°C to 218°C (100°F to 425°F)
<b>Adhesive Viscosity</b>	100 to 20,000 cps*	100 to 20,000 cps*	5,000 to 80,000 cps**	100 to 20,000 cps*	1,000 to 200,000 cps*	1,000 to 200,000 cps*	500 to 30,000 cps*
<b>Application Type</b>	Continuous / Intermittent	Continuous	Continuous	Continuous / Intermittent	Continuous	Continuous	Continuous / Intermittent
<b>Max. Coating Width</b>	25 mm (1 in)	900 mm (35.43 in)	900 mm (35.43 in)	500 mm (19.68 in)	Fix 2,700 mm (106.3 in) Adjust. 1,600 mm (63 in)	2,700 mm (106 in)	550 mm (21.7 in)
<b>Coat Weight Minimum</b>	.5 mil (12 g/m <sup>2</sup> )	.5 mil (12 g/m <sup>2</sup> )	.5 mil (12 g/m <sup>2</sup> )	.5 mil (12 g/m <sup>2</sup> )	.1 mil (3 g/m <sup>2</sup> )	.1 mil (3 g/m <sup>2</sup> ) per side	.5 mil (12 g/m <sup>2</sup> )
<b>Cross-Web Accuracy</b>	± 10%	± 10%	± 10%	± 10%	± 3%	± 3%	± 0.5%
<b>Supply Voltage</b>	200-240 VAC 1 Phase 50-60Hz	200-240 VAC 1 Phase 50-60Hz	200-240 VAC 1 Phase 50-60Hz	200-240 VAC 1 Phase 50-60Hz	200-240 VAC 1 Phase 50-60Hz	200-240 VAC 1 Phase 50-60Hz	200-240 VAC 1 Phase 50-60Hz
<b>Dimensions (HxDxW)</b>	99 x 100.5 x 44mm (3.9 x 3.95x 5.1 x 1.73 in)	335 x 150 x 130-930 mm (13.2 x 5.9 x 5.1-36.6 in)	335 x 150 x 175-975 mm (13.2 x 5.9 x 6.9-38.4 in)	241 x 93 x 50-510 mm (9.5 x 3.6 x 1.9-20 in)	Fix 800x521x460-3,000 mm (31.5x20.51x18.11-118.11 in) Adjust. 800x521xcustom (31.5x20.51xcustom)	Custom	272 x 222 x 700-1600 mm (10.71 x 8.74 x 27.56-63.03 in)

Note: All above information is dependent on line speed operation and type of adhesive, some results may vary. \* Adhesive dependent \*\* Depending on adhesive rheology