

## ECCO POWER FLOW 522S



Ecco Power Flow 522S is particularly suitable for craftsmen as an additional unit and for industrial painting jobs. The Ecco 522S qualifies for the machine building, wood furniture, steel and vehicle industries. It is suitable for anyone who uses a variety of painting materials. The pump also qualifies for manual and automated installations feeding one or more spray guns. These Ecco Power Flow pumps can easily be rebuilt into a AA (air assisted) pump, and can be delivered bare, on a tripod, on a trolley or on a wall bracket.

### TECHNICAL DATA

Pressure Ratio	22:1
Max spray volume (cc/min)	
Capacity (cc/double stroke)	110
Paint connection, suction/pressure	G1 male and 1/4 NPSM
Max air inlet pressure, bar (psi)	8 (116)
Max air consumption (lit/min)	900
Air inlet connection	
Air outlet connection	
Max output pressure (Bar/Psi)	176 (2552)

PUMP TYPE	TYPE OF ASSEMBLY	ORDERING NUMBER	WEIGHT
522S-A	Bare pump	8621 0716 00	22 kg
522S-B-A	Bracket for wall	8621 071601	25 kg
522S-B-AA	Bracket for wall	8621 0716 02	25 kg
522S-T-A	Trolley	8621 0716 03	24 kg
522S-T-AA	Trolley	8621 0716 04	24 kg

NEZÁVAZNÁ POPTÁVKA